

C4/6.SF



TE Connectivity has acquired the DIN Rail Terminal Block product range from ABB

Products → Low Voltage Products and Systems → Connection Devices → Terminal Blocks → SNACompact Series

General Information

C4/6.SF

1SNL506410R0000

3472599857032

C4/6.SF

- Protect your circuits with 5x20 fuse terminal block compliant with IEC 609 47-7-3 (Fuse not supplied with the terminal blocks), -Same profile as C2.5/ 5 or C4/6 feed through terminal block for aligned marking and wiring

Ordering

Grey, Black

50 piece

85369010

Popular Downloads

1SNC160028L0202

1SNC160028L0202

Dimensions

6 mm

43.6 mm

64 mm

11.8 g

Technical

4 mm²

6 mm

Screw clamp

Fuse

Screw Clamp / Flexible 1x 0.2 ... 4 mm²

Screw Clamp / Flexible 2x 0.2 ... 2.5 mm²

Screw Clamp / Rigid 1x 0.2 ... 6 mm²

Screw Clamp / Rigid 2x 0.2 ... 2.5 mm²

Screw Clamp / With Insulated Ferrule 1x 0.2 ... 4 mm²

Screw Clamp / Without Insulated Ferrule 1x 0.2 ... 4 mm²

Screw Clamp / With Twin Ferrule 2x 0.2 ... 2.5 mm²

A4

Main Circuit 6.3 A

500 V

6000 V

2000 V

3

acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20

Polyamide

TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

acc. IEC 60947-1 0.5 N·m

Manufacturer 0.8 N·m

Technical UL/CSA

Main Circuit 300 V

Screw Clamp / Rigid 1x 24 ... 10 AWG

Screw Clamp / Rigid 2x 24 ... 14 AWG

Screw Clamp / With Insulated Ferrule 1x 24 ... 12 AWG

Screw Clamp / Without Insulated Ferrule 1x 24 ... 10 AWG

Screw Clamp / With Twin Ferrule 2x 24 ... 16 AWG

V0

Environmental

Operation -55 ... +110 °C

Storage -55 ... +110 °C

Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificates and Declarations (Document Number)

1SND161106A0201

1SND225043U1000

1SND161009A1100

1SNC160028L0202

1SND230544F0201

Classifications

X

EC000899 - Fuse terminal block

EC000899 - Fuse terminal block

EC000899 - Fuse terminal block

Container Information

50 piece

65 mm

305 mm

45 mm

0.59 kg

3472599857032

750 piece

250 mm

330 mm

210 mm

8.85 kg

Box